

Section 26 Town 6 Range 6 Dec 14 1896

I commenced a Survey of Section 26, T. 6, R. 6  
and part of 24 & 25  
for \_\_\_\_\_

Frank Graft  
Elijah Carpenter H.B.  
Luther Sylvestor } C. B.

W. W. Glogston  
Surveyor Greene County.

Var.

Course.	Point of Beginning.	Chains Distance.	Corrected Bearings.
North	S E (26)	80.32	N E. 109° ch bank of river 116.26 over river 160.65 S E 14
		60.24	E 4 A E
West	A E	64.00	to White River
		79.36	to A. W.
East	A E	28.10	to White River
		79.77	to A E Sec 25.

Jan 6 1897  
Surveyed for the Trustee of Stafford Tp  
a line for road between Secs 8 & 17 and  
1/2 mile west between Secs 7 & 18 - 6 - 7

November 18<sup>th</sup> 1897  
I surveyed off 2 acres of land for John Shirts off of the North side of  
the NW 1/4 31-6-4. Beginning at NW cor of said tract thence East 17.68 ch to  
the corner in the creek thence South 5 rods thence East 17.68 to the range line thence  
North 5 rods to the beginning excepting lot 80 x 120 feet out of NW corner  
I found no certainty in SW cor 31 as at present located.  
I find by examination of records as well as the tradition of the people  
that the south boundary of Scotland was accepted as the North boundary  
of said NW 1/4 31-6-4 or said line was made the South boundary of the  
town which was prior to 1840 J. C. Brown surveyed the town in 1840.  
So I conclude that to be the line. J. M. Parker Dep. Sur.

CORNER ESTABLISHED.	Monument.	Device.	WITNESS POINTS OR BEARING TREES.	Mark or Dia. in Inches.	COURSE.	Links Distant.	REMARKS.
A E	Stone						The stone for this corner would weigh several hundred pounds
E 1/4 N E	Spike		Coffeenut	30	S 9 1/4 E	15	
SW ch W of A E cor	Stake		Cottonwood	12	N 73 W	13 1/2	
			"	12	S 69 W	12 1/2	
Also at same time re-established the following corners							
A E 36-6-6	Beech			20	N 37 W	107	
	Stone				N 89 1/4 W	38 1/2	
	Stone				S 42 W	54 1/2	
E 1/4 24-6-6	Elm			15	S 77 E	62 1/2	
	"			24	N 75 E	75	

64  
66  
38 1/2  
28 1/2  
42 1/2

Established the following corners

1/4 ch S of NW 17	Stone	Stone	N 47 1/2 E	40
1/4 ch E of NW "	Stone	Stone	N 84 1/2 W	69
1/4 ch South of above cor "	"	"	S 1 W	24

Corners established  
SW cor. lot 1 in Scotland East 30

Feb 23-1897  
Sec 17-T. 6 N. R. 7. W

SW	Stone	J. oak	14"	N 49° E	35.5 ft
"	"	cemet. Post	14"	S 50° E	26.5 "